



# Nikon D90 Rear Case Replacement

This guide outlines the process of taking the rear case off of the D90 to access the insides.

Written By: Ryan Lutz



## Step 1 — Rear Case



- Slide the eyepiece up and off the viewfinder.

## Step 2



- Using a PH000 screwdriver, remove the two 4.8mm Phillips screws from the back of the viewfinder.
- ⚠ Some screws may be JIS. Be wary of this if your PH000 does not feel like it is properly gripping the screws.



## Step 3



- Remove the two 6.4mm Phillips screws on the right side of the camera, near the SD card slot.

## Step 4



- Remove the two 6.4mm Phillips screws on the left side of the camera, near the I/O ports.

## Step 5



- On the bottom of the camera,
  - remove the two 5.3mm Phillips screws
  - and the other two 6.3mm Phillips screws.

## Step 6



- Using a spudger, separate the bottom panel from the rear case just enough to clear the two clips on the rear casing in the next step.

## Step 7



- Lift the rear case off of the back of the camera.

⚠ Don't pull the casing completely off yet, as the ribbon cables are still connected.

- Be mindful of the two clips, making sure to keep the bottom panel far enough away to clear them.

## Step 8



- Set the rear casing off to the side so you can access the ZIF connectors.

**i** The orientation shown in the picture seems to be the best position for the casing to sit comfortably without stressing the ribbon cable connections.



## Step 9



- Disconnect the ribbon cables from their respective ZIF connectors on the logic board.

## Step 10



- Separate the rear casing from the camera.

To reassemble your device, follow these instructions in reverse order.

This document was last generated on 2017-06-29 04:30:54 PM.